



US005737053A

United States Patent [19]**Yomogihara et al.**[11] **Patent Number:** **5,737,053**[45] **Date of Patent:** **Apr. 7, 1998**

[54] **WIRE SUBSTRATE HAVING BRANCH LINES PERPENDICULAR TO THE MAIN LINES IN WHICH THE BRANCH LINES CONNECT TO DRIVING CIRCUITS ON A DISPLAY DEVICE**

4,831,278 5/1989 Ueda et al. 174/72 A
 4,955,695 9/1990 Kubo et al. 349/151
 5,349,226 9/1994 Kawaguchi et al. 349/152
 5,563,445 10/1996 Iijima et al. 257/698

[75] **Inventors:** **Yoshikazu Yomogihara; Ikue Yoshida,**
 both of Tokyo, Japan

FOREIGN PATENT DOCUMENTS

3-231488 10/1991 Japan 439/67
 5-107551 4/1993 Japan .

[21] **Appl. No.:** **658,267**

[22] **Filed:** **Jun. 5, 1996**

[30] **Foreign Application Priority Data**

Jun. 5, 1995 [JP] Japan 07-137756
 Apr. 2, 1996 [JP] Japan 08-80074

[51] **Int. Cl.⁶** **G02F 1/1345; H05K 1/00;**
H01R 9/09

[52] **U.S. Cl.** **349/149; 349/150; 349/151;**
361/749; 439/67; 439/77

[58] **Field of Search** **174/72 A, 254,**
174/255, 260; 439/67, 77; 361/749; 349/149,
150, 151, 152, 158, 160

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,214,725 10/1965 De Rose et al. 439/67

Primary Examiner—William L. Sikes

Assistant Examiner—Walter Malinowski

Attorney, Agent, or Firm—Cushman Darby & Cushman IP
 Group of Pillsbury Madison & Sutro LLP

[57] **ABSTRACT**

There is provided a liquid crystal display device in which the area of a peripheral portion of the glass substrate can be reduced and which can be packaged easily. Three X-side IC chips 22 are directly mounted to a peripheral portion 18 of a glass substrate 14 that constitutes a display portion 16 of a liquid crystal display device 10. Pads 27 for the X-side IC chips 22 are disposed between the X-side IC chips 22. A branch region 32 projecting from a main region 30 of a flexible substrate 28 is disposed between the X-side chips 22. Terminals 38 provided in the branch region 32 are electrically connected to the pads 27.

18 Claims, 15 Drawing Sheets